


TERMINALES AISLADAS TIPO ANILLO

Características

Material: cobre estañado.

Material del aislante: vinilo



Referencias


Referencia	Dimensiones					Calibre Alambre			Color
	d2Ø	B	L	H	DØ	Simple mm²	Trenzado mm²	AWG	
VTA-1.25-3	3.7	5.5	16.3	11	4.0	0.5 ~ 1.5	0.25 ~ 1.65	22 ~ 16	Rojo
VTA-1.25-4	4.3	8.0	18.3	11	4.0				
VTA-1.25-5	5.3	8.0	18.3	11	4.0				
VTA-2-3	3.7	8.5	18.7	11	4.5	1.5 ~ 2.5	1.04 ~ 2.63	16 ~ 14	Azul
VTA-2-4	4.3	8.5	18.7	11	4.5				
VTA-2-5	5.3	9.5	18.2	11	4.5				
VTA-2-6	6.4	12.0	22.0	11	4.5				
VTA-5.5-5	5.3	9.5	26.3	13.7	6.3	4.0 ~ 6.0	2.63 ~ 6.64	12 ~ 10	Amarillo
VTA-5.5-6	6.4	11.0	28.0	13.7	6.3				
VTA-5.5-8	8.4	15.0	34.0	13.7	6.3				
VTA-8-6	6.4	11.0	31.5	17.5	8.3	10	6.64 ~ 10.52	8	Rojo

TERMINALES AISLADAS TIPO "U"

Características

Material: cobre estañado

Material del aislante: vinilo



Referencias

Referencia	Dimensiones					Calibre Alambre			Color
	d2Ø	B	L	H	DØ	Simple mm²	Trenzado mm²	AWG	
VTU-1.25-3	3.7	5.7	21	11	4.0	0.5 ~ 1.5	0.25 ~ 1.65	22 ~ 16	Rojo
VTU-1.25-4	4.3	6.4	21	11	4.0				
VTU-2-3	3.2	5.7	21	11	4.5	1.5 ~ 2.5	1.04 ~ 2.63	16 ~ 14	Azul
VTU-2-4	4.3	7.2	21	11	4.5				
VTU-2-5	5.3	8.0	21	11	4.5				
VTU-2-6	6.4	10.7	21	11	4.5				
VTU-5.5-4	4.3	8.2	24.7	13.7	6.3	4.0 ~ 6.0	2.63 ~ 6.64	12 ~ 10	Amarillo
VTU-5.5-5	5.3	9.0	24.7	13.7	6.3				
VTU-8-6	6.4	12.0	32	17.5	8.3	10	6.64 ~ 10.52	8	Rojo